

Projection/Optical Single ended GY9.5




Fig. 1




Fig. 2




Fig. 3




Fig. 4






Fig. 5

BASE TYPE



GY9.5 (B)



GY9.5 (C3)

PHYSICAL DATA AND CHARACTERISTICS

Type	ANSI Ref.	Volts (V)	Watts (W)	Approx. Initial Lumens (lm)	Colour Temp. (K)	Std. Pkg. Qty	Rated Av. Life (hrs)	Dimensions mm (in)			Filament	Fig. No.
								M.D.	M.O.L.	L.C.L.		
Medium prefocus 2 pin base - GY9.5												
JC12V100W10H/B	DZZ	12	100	2300	3100	20	1000	11.0 (.4)	52 (2.1)	27 (1.1)	C-Bar-6	1
FDT12V100W	FDT	12	100	2700	3300	20	50	11.0 (.4)	52 (2.1)	27 (1.1)	C-Bar-6	2
FDS24V150W	FDS	24	150	4600	3400	20	50	13.5 (.5)	60 (2.4)	33 (1.3)	C-Bar-6	3
DZE24V150W	DZE	24	150	4300	3250	20	100	13.5 (.5)	60 (2.4)	33 (1.3)	C-Bar-6	3
JCD650WS/B	EKD	120	650	17500	3200	20	75	22.0 (.9)	63 (2.5)	36.5 (1.4)	CC-6	4
JCD650WC/B	—	120	650	18200	3200	20	50	22.0 (.9)	66 (2.6)	36.5 (1.4)	CC-6	4
JCD1000WC/C3	—	120	1000	26000	3200	20	75	26.0 (1)	75 (3.0)	46 (1.8)	2CC-8	5
JCD1000WC/C3	—	220/230	1000	26000	3100	20	75	26.0 (1)	80 (3.1)	46 (1.8)	2CC-8	5
JCD1000WC/C3	—	240/250	1000	26000	3100	20	75	26.0 (1)	80 (3.1)	46 (1.8)	2CC-8	5

Notes: • Burning Position: Universal