


Stage/Studio

Double ended R7s base, CC-8 filament



PHYSICAL DATA AND CHARACTERISTICS

Type	ANSI Ref.	Volts (V)	Watts (W)	Approx. Initial Lumens (lm)	Colour Temp. (K)	Std. Pkg. Qty	Rated Av. Life (hrs)	Dimensions mm (in)			
								M.D.	M.O.L.	LL	C. to B.
R7s base, CC-8 filament, clear bulb											
JPD250W	DXM	30	250	8400	3400	10	12	14.0 (.6)	59.6 (2.3)	8.0 (.3)	56.6 (2.2)
JPD375W	DWZ	30	375	7000	2900	10	1000	14.0 (.6)	79.3 (3.1)	10.0 (.4)	76.3 (3.0)
JPD400WC	FDA	120	400	10400	3200	10	250	14.0 (.6)	79.3 (3.1)	25.0 (1.0)	76.3 (3.0)
JPD400W20H	EHR	120	400	6400	2900	10	2000	14.0 (.6)	79.3 (3.1)	20.0 (.8)	76.3 (3.0)
JPD420WC	FAL	120	420	11000	3200	10	75	14.0 (.6)	66.6 (2.6)	14.0 (.8)	63.6 (2.5)
JPD600WC	FFJ	120	600	16500	3200	10	75	14.0 (.6)	66.7 (2.6)	19.0 (.8)	63.6 (2.5)
JPD600WC	FCB	120	600	16500	3200	10	75	14.0 (.6)	95.3 (3.8)	19.0 (.8)	92.3 (3.6)
JPD600WC	FEB, A1/228	220/230	600	15000	3200	10	75	15.2 (.6)	93.6 (3.7)	17.8 (.7)	92.3 (3.6)
JPD600WC	FEA, A1/228	240	600	15000	3200	10	100	14.0 (.6)	95.1 (3.7)	27.0 (1.1)	92.3 (3.6)
JPD650WC	FAD	120	650	16250	3200	10	100	14.0 (.6)	79.3 (3.1)	25.0 (1.0)	76.3 (3.0)
JPD650WC	—	220/230	650	16250	3200	10	100	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD650WC	—	240/250	650	16250	3200	10	100	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD650WC	—	240	650	16250	3200	10	100	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD650WS	—	220/230	650	19500	3400	10	25	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD650WS	—	240	650	19500	3400	10	25	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD650WS	DWY, P1/9	115/120	650	19500	3400	10	25	14.0 (.6)	79.3 (3.1)	26.0 (1.0)	76.3 (3.0)
JPD800WC	DXX	220/230	800	20000	3200	10	75	14.0 (.6)	79.3 (3.1)	29.0 (1.1)	76.3 (3.0)
JPD800WC	DXX	240	800	20000	3200	10	75	14.0 (.6)	79.3 (3.1)	29.0 (1.1)	76.3 (3.0)
JPD1000WS	DXB	120	1000	31000	3400	10	35	16.0 (.6)	95.0 (3.7)	25.0 (1.0)	92.1 (3.6)
JPD1000WC	DXW	120	1000	28000	3200	10	150	16.0 (.6)	95.0 (3.7)	25.0 (1.0)	92.1 (3.6)
JPD1000WC	DYN	120	1000	24500	3100	10	150	15.2 (.6)	111.1 (4.4)	27.9 (1.1)	108.1 (4.3)
JPD1000WC	DYA	120	1000	28000	3200	10	200	16.0 (.6)	111.1 (4.4)	27.9 (1.1)	108.1 (4.3)
JPD1000WC	DWT	120	1000	23400	3000	10	2000	17.8 (.7)	142.9 (5.6)	20.3 (.8)	138.5 (5.5)
JPD1000WC	FER	120	1000	27500	3200	10	500	17.8 (.7)	142.9 (5.6)	20.3 (.8)	138.5 (5.5)
JPD2000WC	FEY	120	2000	57000	3200	10	50	25.0 (1)	142.9 (5.6)	25.0 (1.0)	138.5 (5.5)
JPD2000WC	FEX	220/230	2000	50000	3200	10	200	26.0 (1)	142.9 (5.6)	40.0 (1.6)	139.7 (5.5)
JPD2000WC	FEX	240/250	2000	50000	3200	10	200	26.0 (1)	142.9 (5.6)	40.0 (1.6)	139.7 (5.5)

Notes: • Burning Position: Universal