


MR16 10,000 hours life



PHYSICAL DATA AND CHARACTERISTICS

Type	Ref. ANSI	Volts (V)	Watts (W)	Base	Std. Pkg. Qty.	Axis Cd (cd)	Colour Temp. (K)	Beam Angle (°)	Rated Av. Life (hrs)
MR16 10,000 hrs with cover glass									
JR8251	ESX	12	20	GU5.3	12	4000	2950	9	10000
JR8252	BBF	12	20	GU5.3	12	880	2950	23	10000
JR8253	BAB	12	20	GU5.3	12	500	2950	38	10000
JR8351	FRB	12	35	GU5.3	12	7400	3050	12	10000
JR8352	FRA	12	35	GU5.3	12	2200	3050	22	10000
JR8353	FMW	12	35	GU5.3	12	1100	3050	36	10000
JR8551	EXT	12	50	GU5.3	12	9500	3050	12	10000
JR8552	EXZ	12	50	GU5.3	12	3100	3050	25	10000
JR8553	EXN	12	50	GU5.3	12	1650	3050	38	10000
MR16 10,000 hrs UV-cut with cover glass									
JR8231	ESX	12	20	GU5.3	12	4000	2950	9	10000
JR8232	BBF	12	20	GU5.3	12	880	2950	23	10000
JR8233	BAB	12	20	GU5.3	12	500	2950	38	10000
JR8331	FRB	12	35	GU5.3	12	7400	3050	12	10000
JR8332	FRA	12	35	GU5.3	12	2200	3050	22	10000
JR8333	FMW	12	35	GU5.3	12	1100	3050	36	10000
JR8531	EXT	12	50	GU5.3	12	9500	3050	12	10000
JR8532	EXZ	12	50	GU5.3	12	3100	3050	25	10000
JR8533	EXN	12	50	GU5.3	12	1650	3050	38	10000
MR16 high colour temp. UV-cut with cover glass									
JR8371	FRB	12	35	GU5.3	12	4200	3450	12	10000
JR8372	FRA	12	35	GU5.3	12	1400	3450	23	10000
JR8373	FMW	12	35	GU5.3	12	880	3450	36	10000
JR8571	EXT	12	50	GU5.3	12	5300	3450	12	10000
JR8572	EXZ	12	50	GU5.3	12	2250	3450	25	10000
JR8574	EXN	12	50	GU5.3	12	1300	3450	36	10000

10,000 hours life MR16 low voltage halogen lamp with cover glass.

FEATURES

- Provides a life nearly equal to some HID products.
- Precise optical design
- Long lasting dichroic coating.
- Suitable for retail stores, lounges, offices, landscape lighting, display cases.